

Show Configured Input Services

Jun 2017

To display configured Input services, use the following command (after mondo halodb)

```
db.input.find()
```

The output will look similar to:

```
{ "_id" : ObjectId("594102c7818fca0ed83551da"), "public_id" : "service1", "name" : "Service1",  
  "created_at" : ISODate("2017-06-14T09:32:55.262Z"), "updated_at" : ISODate("2017-06-14T09:32:57.525Z"),  
  "version" : "1.9.0", "gop_signaling" : "EBP", "gop_duration" : 2000, "sources" : [ { "port" : 10001,  
    "address" : "239.0.200.1" }, { "port" : 10002, "address" : "239.0.200.1" }, { "port" : 10003, "address"  
    : "239.0.200.1" }, { "port" : 10004, "address" : "239.0.200.1" } ], "multicast_sources" : [ ],  
  "created_by_dvr" : false }  
{ "_id" : ObjectId("59413043818fca5a01232e8c"), "public_id" : "service2", "name" : "Service2",  
  "created_at" : ISODate("2017-06-14T12:46:59.451Z"), "updated_at" : ISODate("2017-06-14T12:46:59.451Z"),  
  "version" : "1.9.0", "gop_signaling" : "EBP", "gop_duration" : 2000, "sources" : [ { "port" : 10001,  
    "address" : "239.0.200.1" }, { "port" : 10002, "address" : "239.0.200.1" }, { "port" : 10003, "address"  
    : "239.0.200.1" }, { "port" : 10004, "address" : "239.0.200.1" } ], "multicast_sources" : [ ],  
  "created_by_dvr" : false }
```

The unit I ran this command on had two configured services, Service1 and Service2.

From:

<https://wiki.alanwalker.uk/> - WalkerWiki - wiki.alanwalker.uk

Permanent link:

https://wiki.alanwalker.uk/doku.php?id=show_configured_inputs&rev=1497518096

Last update: 2023/03/09 22:35

